

AUTOMOTIVE

Deka®

INTIMIDATOR®

AGM

FEATURES AND BENEFITS

- Premium maintenance-free starting and cycle service power
- 20x more vibration protection* safeguards battery performance over time
- Faster recharging powers more electronics longer
- 2x the cycle life* extends performance and life
- Spillproof design provides added protection for sophisticated electronic equipment

* Compared to conventional designs



Conventional automotive batteries can be extremely intimidated by the power demands of today's vehicles – falling short of delivering critical dependability and performance. Cars, trucks, SUVs, and other passenger vehicles have more electronics than ever before.

Intimidator automotive batteries are especially designed to handle factory installed electronics to anything that plugs in or turns on, and still deliver dependable starting power. With almost **2x the endurance*** in severe service and **2x the cycle life***, these batteries are equipped for the toughest conditions and the most intense electrical power demands.

Intimidator automotive batteries are also ideal for tuner cars or off-road vehicles, offering superior power for high-performance equipment and a high-impact design for rugged, back road adventures.



Intimidator® AGM Solutions for Intimidating Battery Needs

Intimidator is a pioneer brand in the development of the form, fit, and function of AGM battery technology. It has been tested and proven to best meet the criteria of the automotive industry.




ADVANCED DURABILITY DESIGNS

- Fortified posts, straps, and welds resist vibration damage
- Maximize current transfer over life of battery



POWER-PERFORM® FULL-FRAME POSITIVE & NEGATIVE PLATES

- Better withstands severe service demands
- Prevents life-robbing electrical shorts from exposed wire



ENHANCED ELECTROLYTE SUSPENSION SYSTEM

- Absorbs more electrolyte, protects internal components
- Micro-porous glass separators prevents acid spills and terminal corrosion

AUTOMOTIVE INTIMIDATOR® AGM BATTERIES

GROUP NUMBER	PART NUMBER	PERFORMANCE LEVEL				WEIGHT (lbs.)	MAXIMUM OVERALL DIMENSIONS						FOOTNOTES
		CCA @ 0°F	R.C.	CA @ 32°F	20 HR CAP		Length		Width		Height		
							in	mm	in	mm	in	mm	
ABSORBED GLASS MAT (AGM) VALVE REGULATED													
75/86	9A75DT	640	100	755	50	41	9 ¹ / ₁₆	242	7 ¹ / ₁₆	179	7 ¹ / ₁₆	202	2,13,16,17,18,22,37,38,39
34/78	9A78DT	775	120	890	55	43	10 ³ / ₁₆	273	6 ³ / ₁₆	175	8	203	2,13,16,17,38,39
24F	9A24F	710	110	875	65	44.5	11 ¹ / ₁₆	282	6 ³ / ₁₆	168	9	229	2,13,17
34	9A34	775	120	890	55	42.5	10 ³ / ₁₆	273	6 ³ / ₁₆	175	8	203	2,13,17,37,38,39,78
34R	9A34R	775	120	890	55	42.5	10 ³ / ₁₆	273	6 ³ / ₁₆	175	8	203	2,13,17,37,38,39,78
35/85	9A35/85	640	100	755	50	40	9 ¹ / ₁₆	242	6 ³ / ₁₆	171	7 ³ / ₁₆	197	2,13,17,18,37,38,39
47 (H5/L2)	9A47	600	100	690	60	39	9 ¹ / ₁₆	242	6 ³ / ₁₆	175	7 ¹ / ₂	190	13,17,22,38,39
48 (H6/L3)	9A48	760	120	875	70	46.5	11	278	6 ³ / ₁₆	175	7 ¹ / ₂	190	13,17,22,38,39
49 (H8/L5)	9A49	850	170	975	92	58	13 ¹⁵ / ₁₆	354	6 ³ / ₁₆	175	7 ¹ / ₂	190	13,17,22,38,39
65	9A65	750	150	860	75	47.5	12	305	7 ³ / ₁₆	187	7 ³ / ₁₆	194	2,13,17,38,39
78	9A78	775	120	890	55	43	10 ³ / ₁₆	273	6 ³ / ₁₆	175	7 ³ / ₁₆	184	2,13,17,38,39
94R (H7/L4)	9A94R	800	140	920	80	52	12 ¹ / ₁₆	315	6 ³ / ₁₆	175	7 ¹ / ₂	190	13,17,22,38,39
95R (H9/L6)	9A95R	950	190	1050	105	64.5	15 ¹ / ₂	394	6 ³ / ₁₆	175	7 ¹ / ₂	190	13,17,22,24,38,39
S46B24R	9A51P	325	60	390	46	29.5	9 ¹ / ₄	235	5	127	8 ³ / ₁₆	220	13,22,38,39,J

All batteries have SAE automotive posts unless noted. All batteries in Black cover/Black case except where noted.

FOOTNOTES:

- | | | |
|---|---|--|
| 2. Black cover / Gray case | 22. Flush manifold vented cover | 39. "Non-spillable" defined by ICAO (International Civil Aviation Organization) and IATA (International Airline Transport Association) definitions |
| 13. Absorbed Glass Mat Technology (AGM) | 24. CCA is EN rating | 78. Shipped with 22mm height adapter |
| 16. Dual terminal, universal design | 37. For height with adapter add 7/8" (22mm) | J. Pencil Posts |
| 17. Includes handle | 38. "Non-spillable" defined by DOT (Department of Transportation) definitions | |
| 18. Includes height adapter, if needed | | |

Experience the East Penn Advantage

East Penn's A³™ Advanced-Cubed precision-focused manufacturing approach ensures the process behind the technology delivers critical quality at each stage of battery production. INTIMIDATOR batteries are supported by A³ manufacturing to optimize the life, power, and durability of the battery's design and performance.



PROPOSITION 65 WARNING: Battery posts, terminals and related accessories contain lead and lead compounds, chemicals known to the State of California to cause cancer and reproductive harm. Batteries also contain other chemicals known to the State of California to cause cancer. **WASH HANDS AFTER HANDLING.**



QUALITY SYSTEM CERTIFIED
ISO 9001
ISO/TS 16949
ENVIRONMENTAL SYSTEM CERTIFIED
ISO 14001



www.dekabatteries.com



East Penn Manufacturing Co. Lyon Station, PA 19536-0147 Phone: 610-682-6361 Fax: 610-682-4781 Order Department Hotline: 610-682-4231