



5043 Farlin Ave.  
St. Louis, MO 63115  
www.associatedequip.com  
314-385-5178

# Product Bulletin

## MODEL 9425

**20 Amp / 25 Amp Peak  
Output Bench Charger /  
Power Supply for  
Standard Automotive,  
Deep-Cycle, AGM and  
Gel Cell batteries**



### Specifications:

Model Number	9425
DC Output	20 Amps
DC Leads	6 ½' 10 AWG
Clamp Rating	300A
Limited Warranty	One Year
Shipping Dimensions	14"x11.5"x11.5"
Weight	21 LBS
AC Cord / Voltage	6' 18-3 / 120VAC 60 Hz
Battery Types	12 Volt Flooded, AGM, and Gel Cell batteries - including Spiral Cell, Orbital, or Optima batteries
Display	3 LED display indicating charge status

### Features:

- **Electrical Stability System (ESS™)**  
technology turns 9425 into a stable power supply for extended service procedures or re-flashes. Nominal 13.9V DC Output
- Program for deep discharge recovery of flooded batteries
- Patented diagnostics indicate weak or defective battery
- Charges all types of 12 volt batteries.
- Designed for AGM, Gel Cell, Sealed, and Standard Flooded batteries including Spiral Cell, Orbital, or Optima batteries
- Dead Battery Override Control
- Made in USA