


Intimidator® AGM Solutions for Intimidating Battery Needs

Intimidator is a pioneer brand in the development of the form, fit, and function of AGM battery technology. It has been tested and proven to best meet the demand of even the most extreme power sports enthusiasts.



POWER-PERFORM FULL-FRAME POSITIVE & NEGATIVE PLATES

- Better withstands severe service demands
- Prevents life-robbing electrical shorts from exposed wire
- 1. Safety Relief Valve System ensures no-leak safety and extends premium performance
- 2. Molded Top and Side Connection Terminals provides ease of installation, increased strength, and durability
- 3. Fortified Posts, Straps, and Welds resist vibration damage, maximize current transfer
- 4. Heavy-Duty Power-Perform Plates optimizes battery's power and energy storage capacity
- **5. Enhanced Electrolyte Suspension System** completely absorbs electrolyte for spillproof design
- 6. Optimized Component Compression provides superior vibration resistance
- Ultra-Pure Demineralized Electrolyte precision filled for extended life
- Stainless Steel Terminal Bolts (not shown) prevent corrosion on battery and equipment



POWER SPORTS INTIMIDATOR® AGM BATTERIES

PART NO.	PERFORMANCE LEVEL		APPROX.	MAXIMUM OVERALL DIMENSIONS						
	CCA	10 AH	WEIGHT (lbs.)	Length		Width		Height		FOOTNOTES
	@ 0°F	RATE		inch	mm	inch	mm	inch	mm	
POWER SPORTS ABSORBED GLASS MAT (AGM) VALVE REGULATED										
ETX9	120	8	6.3	5%	150	37/16	88	4 ¾6	106	2,38,39
ETX12	180	10	9.4	5%	150	37/16	88	51/8	130	2,38,39
ETX14	220	12	12	5%	150	37/16	88	5¾	145	2,38,39,42,75
ETX14L	220	12	12	5%	150	37/16	88	5¾	145	2,38,39
ETX15	220	14	11	51/4	134	3½	90	6 %6	166	2,38,39,42,76
ETX15L	220	14	11	51/4	134	3½	90	6 %6	166	2,38,39
ETX16	325	19	17	6%	175	4	100	61/8	155	2,38,39,42,74
ETX16L	325	19	17	6%	175	4	100	61/8	155	2,38,39,42,74
ETX18L	340	20	18	81/8	206	3%6	91	6%	163	2,38,39
ETX20L	310	17.5	15.5	6%	175	37/16	88	61/4	155	2,38,39
ETX30LA	400	26	21.7	6%	168	5 ¾6	131	7 ¾	197	2,38,39,78

FOOTNOTES: 2. Black cover / Gray case 38. "Non-spillable" defined by DOT (Department of Transportation) definitions 39. "Non-spillable" defined by ICAO (International Commercial Airline Organization) and IATA (International Airline Transport Association) definitions 42. Height without adapter 74. Shipped with 20mm adapter 75. Shipped with two (2) 17mm adapters 76. Shipped with 10mm adapter 78. Shipped with 22mm height adapter X. 3/8" x 1/16" stainless steel stud posts

Experience Quality at its Core

East Penn's $A^{3 \text{ TM}}$ Advanced-Cubed precision-focused manufacturing approach ensures the process behind the technology delivers core quality at each stage of battery production. INTIMIDATOR batteries are supported by A³ manufacturing to optimize the life, power, and durability of the battery's design and performance.



EAST PENN manufacturing Co., inc. Lyon Station, PA 19536-0147 • Phone: 610-682-6361 • Fax: 610-682-4781 Order Department Hotline: 610-682-4231 • www.dekabatteries.com

Lyon Station, PA 19536-0147 • Phone: 610-682-6361 • Fax: 610-682-4781



